



STANDARD PEDESTAL OF
LENEXA, KANSAS

SINGLE METER SERVICE PEDESTAL

TYPICAL APPLICATIONS INCLUDE PARKING LOT LIGHTING, HIGHWAY, STREET AND SIGN LIGHTING AND TRAFFIC SIGNAL CIRCUITS.

STANDARD FEATURES

- METER SOCKET 5 th clip JAW ASSY
- UTILITY LANDING LUGS 250 KCMIL
- STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE
- CIRCUIT BREAKER INTERIOR COPPER BUS 12 CIRCUIT
- LIGHTING ARRESTER AVAILABLE 650 VAC
- MERCURY RELAY AND TERMINAL BLOCK FOR EACH LIGHTING CIRCUIT AS REQUIRED
- DOOR STOP TO PREVENT CUSTOMER DOOR SWINGING CLOSED
- RECEPTACLE GFI
- PHOTOELECTRIC SOCKET

SPECIFICATIONS

- * NEMA 3R CONSTRUCTION
- * .125 ALUMINUM NON-ANODIZED
- * AVAILABLE IN STEEL W/ POWDER COAT FINISH

- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE